

Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	29-6122-5	Version Number:	1.03
Revision Date:	18/05/2017	Supercedes Date:	12/12/2016

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) and its modifications

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

G95, Hot Rims® All Wheel and Tire Cleaner (24-57A): G9524

Product Identification	Numbers			
14-1000-0999-3	14-1000-1000-9	14-1000-1001-7	14-1000-1002-5	14-1000-1003-3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Automotive

1.3. Details of the supplier of the safety data sheet

ADDRESS:	GR_GCSL - Local CUNO Address
Telephone:	GR_GCSL - Local Meguiar's Telephone
E Mail:	GR_GCSL - Local Meguiar's Email
Website:	GR_GCSL - Local Meguiar's Website

1.4. Emergency telephone number

GR_GCSL - Local Meguiar's Emergency Telephone

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Substance or Mixture Corrosive to Metals, Category 1 - Met. Corr. 1; H290 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Corrosion/Irritation, Category 1A - Skin Corr. 1A; H314 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD Danger

Symbols: GHS05 (Corrosion) |

Pictograms



HAZARD STATEMENTS	
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H412	Harmful to aquatic life with long lasting effects.
PRECAUTIONARY STAT	TEMENTS
General:	
P102	Keep out of reach of children.
Prevention:	
P234	Keep only in original container.
P260E	Do not breathe vapor or spray.
Response:	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2% of the mixture consists of components of unknown acute dermal toxicity.

Notes on labelling:

Updated per Regulation (EC) No. 648/2004 on detergents. Ingredients required per 648/2004: <5%: Anionic surfactant, EDTA and salts thereof, non-ionic surfactant. Material is classified as skin corrosive 1A per test data

2.3. Other hazards

None known

Ingredient	C.A.S. No.	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	Mixture			75 - 95	Substance not classified as hazardous
Sodium Metasilicate	6834-92-0	229-912-9		< 5	**Skin Corr. 1B**, H314; **STOT SE 3**, H335 **Met. Corr. 1**, H290
Sodium Olefin Sulfonate	68439-57-6	270-407-8		< 5	**Acute Tox. 4**, H302; **Eye Dam. 1**, H318; **Aquatic Chronic 3**, H412
2-Propoxyethanol	2807-30-9	220-548-6		< 5	**Acute Tox. 4**, H312; **Eye Irrit. 2**, H319
Tetrasodium EDTA	64-02-8	200-573-9		< 5	**Acute Tox. 4**, H302; **Eye Dam. 1**, H318
Decylamine Oxide	2605-79-0	220-020-5		< 2	**Skin Irrit. 2**, H315; **Eye Dam. 1**, H318 **Aquatic Acute 1**, H400,M=1; **Aquatic Chronic 1**, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralize spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralizing agent until reaction stops. Let cool before collecting. Or use a commercially available caustic (alkaline or basic) spill clean-up kit. Follow kit directions exactly. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Absorb spillage to prevent material damage. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from acids. Store away from oxidizing agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material Nitrile Rubber Thickness (mm) No data available **Breakthrough Time** No data available

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Boots - Nitrile Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties Physical state Liquid

Appearance/Odor Odor threshold pH Mild odor; Clear *No Data Available* 13.56

>=200 °C				
No Data Available				
Not Applicable				
Not Classified				
Not Classified				
Flash point > 93 °C (200 °F)				
No Data Available				
No Data Available				
No Data Available				
No Data Available				
1.02 - 1.03 [<i>Ref Std</i> :WATER=1]				
Complete				
No Data Available				
No Data Available				
No Data Available				
No Data Available				
No Data Available				
No Data Available				

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization may occur.

10.4. Conditions to avoid Heat

10.5. Incompatible materials Strong acids Strong oxidizing agents

10.6. Hazardous decomposition products <u>Substance</u>

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Sodium Metasilicate	Dermal	Rabbit	LD50 > 4,640 mg/kg
Sodium Metasilicate	Ingestion	Rat	LD50 500 mg/kg
2-Propoxyethanol	Dermal	Rabbit	LD50 1,337 mg/kg
2-Propoxyethanol	Inhalation- Vapor (4 hours)	Rat	LC50 > 11.1 mg/l
2-Propoxyethanol	Ingestion	Rat	LD50 3,089 mg/kg
Sodium Olefin Sulfonate	Dermal	Rat	LD50 > 2,000 mg/kg
Sodium Olefin Sulfonate	Ingestion	Rat	LD50 578 mg/kg
Tetrasodium EDTA	Ingestion	Rat	LD50 1,658 mg/kg
Decylamine Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Decylamine Oxide	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg

 $\overline{ATE} = acute toxicity estimate}$

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro	Corrosive
	data	
Sodium Metasilicate	Rabbit	Corrosive
Sodium Olefin Sulfonate	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	similar health	Corrosive
	hazards	
Sodium Metasilicate	Rabbit	Corrosive
Sodium Olefin Sulfonate	Rabbit	Corrosive

Skin Sensitization

S S		
Name	Species	Value
	_	
Sodium Metasilicate	Mouse	Not classified
Sodium Olefin Sulfonate	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Sodium Metasilicate	In Vitro	Not mutagenic
Sodium Metasilicate	In vivo	Not mutagenic
Sodium Olefin Sulfonate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Sodium Olefin Sulfonate	Dermal	Rat	Not carcinogenic
Sodium Olefin Sulfonate	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Sodium Metasilicate	Ingestion	Not classified for development	Mouse	NOAEL 200 mg/kg/day	during gestation
Sodium Olefin Sulfonate	Ingestion	Not classified for female reproduction	Rat	NOAEL 871 mg/kg	2 generation
Sodium Olefin Sulfonate	Ingestion	Not classified for male reproduction	Rat	NOAEL 891 mg/kg	2 generation
Sodium Olefin Sulfonate	Ingestion	Not classified for development	Rabbit	NOAEL 600 mg/kg	during organogenesis

Target Organ(s)

Specific '	Target	Organ	Toxicity -	single	exposure
Specific	Largu	Organ	IUMICITY -	Single	CAPUSUIC

	Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
--	------	-------	-----------------	-------	---------	-------------	----------

						Duration
Sodium Metasilicate	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Sodium Metasilicate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 2,400 mg/kg/day	4 weeks
Sodium Metasilicate	Ingestion	endocrine system blood	Not classified	Rat	NOAEL 804 mg/kg/day	3 months
Sodium Metasilicate	Ingestion	heart liver	Not classified	Rat	NOAEL 1,259 mg/kg/day	8 weeks
Sodium Olefin Sulfonate	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	6 months
Sodium Olefin Sulfonate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg	6 months

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available

Material	Cas #	Organism	Туре	Exposure	Test Endpoint	Test Result
Decylamine Oxide	2605-79-0	Ricefish	Estimated	96 hours	Lethal Concentration	29.9 mg/l
					50%	
Decylamine Oxide	2605-79-0	Water flea	Estimated	48 hours	Effect Concentration 50%	2.23 mg/l
Decylamine Oxide	2605-79-0	Green algae	Estimated	72 hours	Effect Concentration 50%	0.129 mg/l

Tetrasodium EDTA	64-02-8	Bluegill	Experimental	96 hours	Lethal Concentration	41 mg/l
Tetrasodium EDTA	64-02-8	Water flea	Experimental	48 hours	50% Effect Concentration 50%	57 mg/l
2- Propoxyethanol	2807-30-9	Rainbow Trout	Estimated	96 hours	Lethal Concentration 50%	1,474 mg/l
2- Propoxyethanol	2807-30-9	Green Algae	Estimated	72 hours	Effect Concentration 50%	>1,000 mg/l
2- Propoxyethanol	2807-30-9	Water flea	Estimated	48 hours	Effect Concentration 50%	1,550 mg/l
2- Propoxyethanol	2807-30-9	Crustacea	Estimated	96 hours	Effect Concentration 50%	89.4 mg/l
Sodium Olefin Sulfonate	68439-57-6	Water flea	Experimental	48 hours	Effect Concentration 50%	4.53 mg/l
Decylamine Oxide	2605-79-0	Water flea	Estimated	21 days	No obs Effect Conc	0.36 mg/l
Decylamine Oxide	2605-79-0	Green algae	Estimated	72 hours	No obs Effect Conc	0.005 mg/l
Tetrasodium EDTA	64-02-8	Water flea	Experimental	21 days	No obs Effect Conc	5.5 mg/l
2- Propoxyethanol	2807-30-9	Green Algae	Estimated	72 hours	No obs Effect Conc	130 mg/l
2- Propoxyethanol	2807-30-9	Water flea	Estimated	21 days	No obs Effect Conc	100 mg/l
Sodium Olefin Sulfonate	68439-57-6	Water flea	Estimated	21 days	No obs Effect Conc	0.37 mg/l
Tetrasodium EDTA	64-02-8	Water flea	Experimental	24 hours	Effect Concentration 50%	1,033 mg/l
Tetrasodium EDTA	64-02-8	Water flea	Estimated	21 days	No obs Effect Conc	29 mg/l
Decylamine Oxide	2605-79-0	Green algae	Estimated	72 hours	No obs Effect Conc	0.005 mg/l
Decylamine Oxide	2605-79-0	Green algae	Estimated	72 hours	Effect Concentration 50%	0.129 mg/l
2- Propoxyethanol	2807-30-9	Water flea	Estimated	48 hours	Effect Concentration 50%	1,550 mg/l
Non-Hazardous Ingredients	Mixture		Field		No obs Effect Conc	>1,001 mg/l
Non-Hazardous Ingredients	Mixture		Field		Lethal Concentration 50%	>1,001 mg/l
Sodium Olefin Sulfonate	68439-57-6	Zebra Fish	Experimental	96 hours	Lethal Concentration 50%	2.6 mg/l

Sodium Olefin Sulfonate	68439-57-6	Water flea	Estimated	21 days	No obs Effect Conc	0.37 mg/l
Sodium Olefin Sulfonate	68439-57-6	Water flea	Experimental	48 hours	Effect Concentration 50%	3.48 mg/l
Sodium Metasilicate	6834-92-0	Water flea	Estimated	48 hours	Effect Concentration 50%	1,700 mg/l
Sodium Metasilicate	6834-92-0	Rainbow Trout	Estimated	96 hours	Lethal Concentration 50%	281 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Tetrasodium EDTA	64-02-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sodium Metasilicate	6834-92-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sodium Olefin Sulfonate	68439-57-6	Estimated Biodegradation	28 days	Dissolv. Organic Carbon Deplet	95 % weight	OECD 301E - Modified OECD Scre
2- Propoxyethanol	2807-30-9	Experimental Biodegradation	20 days	Biological Oxygen Demand	100 % weight	Other methods
Decylamine Oxide	2605-79-0	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	97 % weight	OECD 301E - Modified OECD Scre
Sodium Olefin Sulfonate	68439-57-6	Experimental Biodegradation	28 days	Carbon dioxide evolution	70 % weight	OECD 301B - Mod. Sturm or CO2
Tetrasodium EDTA	64-02-8	Estimated Biodegradation	28 days	Biological Oxygen Demand	0 % BOD/ThBOD	OECD 301D - Closed Bottle Test

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Sodium	6834-92-0	Data not	N/A	N/A	N/A	N/A
Metasilicate		available or				
		insufficient for				
		classification				

Non-Hazardous	Mixture	Data not	N/A	N/A	N/A	N/A
Ingredients		available or				
		insufficient for				
		classification				
Decylamine	2605-79-0	Estimated		Bioaccumulatio	180	Est: Bioconcentration
Oxide		Bioconcentrati		n Factor		factor
		on				
Tetrasodium	64-02-8	Experimental	42 days	Bioaccumulatio	123	OECD 305E-Bioaccum
EDTA		BCF-Carp		n Factor		Fl-thru fis
2-	2807-30-9	Estimated		Log of	0.08	Est: Octanol-water part.
Propoxyethanol		Bioconcentrati		Octanol/H2O		coeff
		on		part. coeff		
Sodium Olefin	68439-57-6	Estimated		Log of	0.7	Est: Octanol-water part.
Sulfonate		Bioconcentrati		Octanol/H2O		coeff
		on		part. coeff		
Tetrasodium	64-02-8	Estimated BCF	28 days	Bioaccumulatio	1.8	Bioconcentration:
EDTA		- Bluegill		n Factor		Flow-through

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

Material	CAS No.	Ozone Depletion Potential	Global Warming Potential
non-hazardous ingredients	Mixture	0	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

200129* Detergents containing dangerous substances

SECTION 14: Transportation information

ADR: UN3266 Corrosive Liquid, Basic, Inorganic, N.O.S (Sodium Metasilicate) Class 8, PG III, (E);C5 IATA: UN3266 Corrosive Liquid, Basic, Inorganic, N.O.S (Sodium Metasilicate) Class 8, PG III IMDG: UN3266 Corrosive Liquid, Basic, Inorganic, N.O.S (Sodium Metasilicate) Class 8, PG III, EmS:F-A, S-B

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment Not applicable

SECTION 16: Other information

List of relevant H statements

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 03: Composition/ Information of ingredients table information was added. Section 03: Composition/ Information of ingredients table information was deleted.

Section 09: Relative density information information was modified.

- Section 11: Acute Toxicity table information was modified.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. Greece SDSs are available at GR_GCSL - Local Meguiar's Website