



## Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	26-6562-8	<b>Version Number:</b>	3.01
<b>Revision Date:</b>	20/06/2017	<b>Supersedes Date:</b>	02/06/2017

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) and its modifications

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164

#### Product Identification Numbers

14-1000-1198-1	14-1000-1199-9	14-1000-1200-5	14-1000-1201-3	HB-0041-2884-7
HB-0041-2885-4	KS-9990-0700-2			

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive

#### 1.3. Details of the supplier of the safety data sheet

**ADDRESS:** GR\_GCSL - Local CUNO Address  
**Telephone:** GR\_GCSL - Local Meguiar's Telephone  
**E Mail:** GR\_GCSL - Local Meguiar's Email  
**Website:** GR\_GCSL - Local Meguiar's Website

#### 1.4. Emergency telephone number

GR\_GCSL - Local Meguiar's Emergency Telephone

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

#### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

### 2.2. Label elements CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

Warning

#### Symbols:

GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

#### Pictograms



#### Ingredients:

Ingredient	C.A.S. No.	EC No.	% by Wt
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	265-191-7	< 10

#### HAZARD STATEMENTS:

H315	Causes skin irritation.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system
H412	Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### General:

P102	Keep out of reach of children.
------	--------------------------------

##### Prevention:

P260A	Do not breathe vapors.
-------	------------------------

**Response:**

P332 + P313

If skin irritation occurs: Get medical advice/attention.

**Disposal:**

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SUPPLEMENTAL INFORMATION****Supplemental Hazard Statements:**

EUH208

Contains 3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.. May produce an allergic reaction.

4% of the mixture consists of components of unknown acute oral toxicity.

Contains 9% of components with unknown hazards to the aquatic environment.

**Information required per Regulation (EU) No 528/2012 on Biocidal Products:**

Contains a biocidal product: Contains C(M)IT/MIT (3:1). May produce an allergic reaction.

**Notes on labelling:**

H304 is not required on the label due to the product's viscosity

## 2.3. Other hazards

None known

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	Mixture			50 - 70	Substance not classified as hazardous
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	265-191-7		< 10	**Asp. Tox. 1**, H304; **STOT RE 1**, H372 **Aquatic Chronic 2**, H411 **Flam. Liq. 3**, H226; **Skin Irrit. 2**, H315
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	265-149-8		5 - 9	**Asp. Tox. 1**, H304 **Aquatic Chronic 2**, H411 **Flam. Liq. 3**, H226; **STOT SE 3**, H336; **EUH066**, EUH066
Naphthol Spirits	64742-48-9	265-150-3		3 - 7	**Asp. Tox. 1**, H304 - Nota P **Aquatic Chronic 2**, H411 **Skin Irrit. 2**, H315; **STOT SE 3**, H336
Organic Salt NJTSR# 04499600-6842	Trade Secret			1 - 5	Substance with a Community level exposure limit in the

**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

					workplace
Kaolin, calcined	92704-41-1	296-473-8		1 - 5	Substance not classified as hazardous
Siloxanes and Silicones, di-Me	63148-62-9			1 - 5	Substance not classified as hazardous
SILOXANES AND SILICONES, DI-ME, [[[3-[(2-AMINOETHYL)AMINO]PROPYL]DIMETHOXY]SILYL]OXY]-TERMINATED	71750-80-6			0.5 1.5	**Acute Tox. 4**, H302
Polymer Wax NJTSR# 04499600-6843	Trade Secret			0.5 - 1.5	Substance not classified as hazardous
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	232-455-8		0.1 - 1	**Asp. Tox. 1**, H304
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	55965-84-9			<= 0.00113	**Acute Tox. 3**, H331; **Acute Tox. 3**, H311; **Acute Tox. 3**, H301; **Skin Corr. 1B**, H314; **Skin Sens. 1A**, H317; **Aquatic Acute 1**, H400,M=1; **Aquatic Chronic 1**, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

#### 5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

**7.3. Specific end use(s)**

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Naphthol Spirits	64742-48-9	Manufacturer determined	TWA:100 ppm	
Paraffin oil	8042-47-5	Greece OELs	TWA(as mist)(8 hours):5 mg/m <sup>3</sup>	
Organic Salt NJTSR# 04499600-6842	Trade Secret	Greece OELs	TWA(as Al)(8 hours):2 mg/m <sup>3</sup>	

Greece OELs : Greece. OELs (Decree No. 90/1999, as amended)

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

None required.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
----------------	--------



<b>Appearance/Odor</b>	Sweet, pleasant odor; Creamy purple liquid
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	8 - 9
<b>Boiling point/boiling range</b>	100 °C
<b>Melting point</b>	<i>Not Applicable</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Explosive properties:</b>	Not Classified
<b>Oxidising properties:</b>	Not Classified
<b>Flash Point</b>	Flash point > 93 °C (200 °F)
<b>Autoignition temperature</b>	<i>Not Applicable</i>
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Relative Density</b>	0.945 - 0.965 [ <i>Ref Std:WATER=1</i> ]
<b>Water solubility</b>	Moderate
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	15,000 - 30,000 mPa-s
<b>Density</b>	0.95 - 0.97 g/ml

**9.2. Other information**

<b>Molecular weight</b>	<i>No Data Available</i>
<b>Percent volatile</b>	83.8 % weight [ <i>Test Method:Estimated</i> ]

## SECTION 10: Stability and reactivity

**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat

**10.5. Incompatible materials**

Strong acids

Strong oxidizing agents

#### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

##### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

##### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

##### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Dermal	Rabbit	LD50 > 3,000 mg/kg
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Ingestion	Rat	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 3,160 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
Naphthol Spirits	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Naphthol Spirits	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphthol Spirits	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Siloxanes and Silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and Silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
SILOXANES AND SILICONES, DI-ME, [[[3-[(2-AMINOETHYL)AMINO]PROPYL]DIMETHOXSILYL]OXY]-TERMINATED	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
WHITE MINERAL OIL (PETROLEUM)	Dermal	Rabbit	LD50 > 2,000 mg/kg
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Dermal	Rabbit	LD50 87 mg/kg
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Rabbit	Irritant

**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Naphthol Spirits	Rabbit	Irritant
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
WHITE MINERAL OIL (PETROLEUM)	Rabbit	No significant irritation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Rabbit	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Naphthol Spirits	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
WHITE MINERAL OIL (PETROLEUM)	Rabbit	Mild irritant
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Guinea pig	Not classified
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea pig	Not classified
Naphthol Spirits	Guinea pig	Not classified
WHITE MINERAL OIL (PETROLEUM)	Guinea pig	Not classified
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Human and animal	Sensitizing

**Photosensitization**

Name	Species	Value
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Human and animal	Not sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
MEDIUM ALIPHATIC SOLVENT NAPHTHA	In vivo	Not mutagenic
MEDIUM ALIPHATIC SOLVENT NAPHTHA	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
Naphthol Spirits	In vivo	Not mutagenic
Naphthol Spirits	In Vitro	Some positive data exist, but the data are not sufficient for classification

**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

WHITE MINERAL OIL (PETROLEUM)	In Vitro	Not mutagenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	In vivo	Not mutagenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphthol Spirits	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphthol Spirits	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
WHITE MINERAL OIL (PETROLEUM)	Dermal	Mouse	Not carcinogenic
WHITE MINERAL OIL (PETROLEUM)	Inhalation	Multiple animal species	Not carcinogenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Dermal	Mouse	Not carcinogenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Ingestion	Rat	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Naphthol Spirits	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Naphthol Spirits	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphthol Spirits	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphthol Spirits	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Naphthol Spirits	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Naphthol Spirits	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months

**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

Naphthol Spirits	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Naphthol Spirits	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphthol Spirits	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Naphthol Spirits	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
WHITE MINERAL OIL (PETROLEUM)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
WHITE MINERAL OIL (PETROLEUM)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
MEDIUM ALIPHATIC SOLVENT NAPHTHA	Aspiration hazard
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
Naphthol Spirits	Aspiration hazard
WHITE MINERAL OIL (PETROLEUM)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Kaolin, calcined	92704-41-1		Data not available or insufficient for classification			

**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7		Data not available or insufficient for classification			
Siloxanes and Silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
Organic Salt NJTSR# 04499600-6842	Trade Secret		Data not available or insufficient for classification			
Kaolin, calcined	92704-41-1	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	No obs Effect Conc	>100 mg/l
Kaolin, calcined	92704-41-1	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Polymer Wax NJTSR# 04499600-6843	Trade Secret		Data not available or insufficient for classification			
SILOXANES AND SILICONES, DI-ME, [[[3-[(2-AMINOETHYL)AMINO]PROPYL]DIMETHOXY]SILYL]OXY]-TERMINATED	71750-80-6		Data not available or insufficient for classification			
Naphthol Spirits	64742-48-9		Data not available or insufficient for classification			
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Green Algae	Estimated	72 hours	No obs Effect Level	4 mg/l
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Green Algae	Estimated	72 hours	Effect Level 50%	8.3 mg/l



**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Rainbow Trout	Estimated	96 hours	Lethal Level 50%	20 mg/l
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	55965-84-9	Diatom	Experimental	72 hours	No obs Effect Conc	0.01 mg/l
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	55965-84-9	Water flea	Experimental	48 hours	Effect Concentration 50%	0.18 mg/l
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone.	55965-84-9	Diatom	Experimental	72 hours	Effect Concentration 50%	0.021 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green Algae	Estimated	72 hours	Effect Concentration 50%	1 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Rainbow Trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
WHITE MINERAL OIL (PETROLEUM )	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
WHITE	8042-47-5	Water flea	Estimated	48 hours	Effect Level	>100 mg/l

**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

MINERAL OIL (PETROLEUM )					50%	
WHITE MINERAL OIL (PETROLEUM )	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
WHITE MINERAL OIL (PETROLEUM )	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l

**12.2. Persistence and degradability**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
WHITE MINERAL OIL (PETROLEUM )	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 % weight	OECD 301B - Mod. Sturm or CO2
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREA TED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
SILOXANES AND SILICONES, DI-ME, [[[3-[(2-AMINOETHYL)AMINO]PROPYL]DIMETHOXY]-TERMINATED	71750-80-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polymer Wax	Trade Secret	Data not	N/A	N/A	N/A	N/A

**M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

NJTSR# 04499600-6843		available or insufficient for classification				
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Organic Salt NJTSR# 04499600-6842	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphthol Spirits	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Experimental Biodegradation	28 days	Carbon dioxide evolution	55 % weight	OECD 301B - Mod. Sturm or CO2
3(2H)- Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl- 3(2H)- isothiazolone.	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.3. Bioaccumulative potential**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
WHITE MINERAL OIL (PETROLEUM )	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
MEDIUM ALIPHATIC SOLVENT NAPHTHA	64742-88-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREA TED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
SILOXANES	71750-80-6	Data not	N/A	N/A	N/A	N/A

AND SILICONES, DI-ME, [[3- [(2- AMINOETHY L)AMINO]PR OPYL]DIMET HOXYSILYL] OXY]- TERMINATE D		available or insufficient for classification				
Polymer Wax NJTSR# 04499600-6843	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Non-Hazardous Ingredients	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Organic Salt NJTSR# 04499600-6842	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphthol Spirits	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3(2H)- Isothiazolone, 5-chloro-2- methyl-, mixt. with 2-methyl- 3(2H)- isothiazolone.	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

#### 12.6. Other adverse effects

No information available

## SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste

## **M21, Mirror Glaze Synthetic Sealant 2.0 (26-63A): M2108, M2116, M2164**

incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

### **EU waste code (product as sold)**

080409*	Waste adhesives and sealants containing organic solvents or other dangerous substances
200127*	Paint, inks, adhesives and resins containing dangerous substances

## **SECTION 14: Transportation information**

ADR/IMDG/IATA: Not restricted for transport.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Global inventory status**

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

### **15.2. Chemical Safety Assessment**

Not applicable

## **SECTION 16: Other information**

### **List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.

H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

Section 02: CLP Ingredient table information was modified.

Section 03: Composition/ Information of ingredients table information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Biocumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**Meguiar's, Inc. Greece SDSs are available at GR\_GCSL - Local Meguiar's Website**