

Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	27-6198-9	Version Number:	2.01
Revision Date:	12/07/2017	Supercedes Date:	09/09/2016

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) and its modifications

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

 Product Identification
 Numbers

 14-1000-1206-2
 HB-0041-2883-9
 HB-0041-2893-8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Automotive

1.3. Details of the supplier of the safety data sheet

	11 5
ADDRESS:	GR_GCSL - Local CUNO Address
Telephone:	GR_GCSL - Local Meguiar's Telephone
E Mail:	GR_GCSL - Local Meguiar's Email
Website:	GR_GCSL - Local Meguiar's Website

1.4. Emergency telephone number

GR_GCSL - Local Meguiar's Emergency Telephone

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD Danger

Symbols: GHS02 (Flame) |GHS07 (Exclamation mark) |

Pictograms



Ingredients: Ingredient	C.A.S. No.	EC No.	% by Wt
Naphthol Spirits	64742-48-9	265-150-3	30 - 60

HAZARD STATEMENTS:	
H228	Flammable solid.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General: P102

Keep out of reach of children.

Prevention: P210A

P261A

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapors.

Respo	on	se:
P332	+	P31

Kesponse.	
P332 + P313	
P370 + P378G	

If skin irritation occurs: Get medical advice/attention. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

10% of the mixture consists of components of unknown acute oral toxicity. 10% of the mixture consists of components of unknown acute dermal toxicity. 54% of the mixture consists of components of unknown acute inhalation toxicity. Contains 64% of components with unknown hazards to the aquatic environment.

Notes on labelling:

H304 is not required on the label due to the product's viscosity Nota P applied to CAS 64742-48-9.

2.3. Other hazards

None known

Ingredient	C.A.S. No.	EC No.	REACH Registration No.	% by Wt	Classification
Naphthol Spirits	64742-48-9	265-150-3		30 - 60	**Asp. Tox. 1**, H304 - Nota P **Aquatic Chronic 2**, H411 **Skin Irrit. 2**, H315; **STOT SE 3**, H336
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	265-149-8		10 - 30	**Asp. Tox. 1**, H304 **Aquatic Chronic 2**, H411 **Flam. Liq. 3**, H226; **STOT SE 3**, H336; **EUH066**, EUH066
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	73138-45-1	277-291-8		7 - 13	Substance not classified as hazardous
Siloxanes and Silicones, di-Me	63148-62-9			7 - 13	Substance not classified as hazardous
CARNAUBA WAX	8015-86-9	232-399-4		3 - 7	Substance not classified as hazardous
PARAFFIN WAX	8002-74-2	232-315-6		0.5 - 1.5	Substance with a Community level exposure limit in the workplace

SECTION 3: Composition/information on ingredients

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop,

get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Naphthol Spirits	64742-48-9	Manufacturer determined	TWA:100 ppm	
		uctermineu		
PARAFFIN WAX	8002-74-2	Greece OELs	TWA(as fume)(8 hours):2	
			mg/m3;STEL(as fume)(15	
			minutes):6 mg/m3	

Greece OELs : Greece. OELs (Decree No. 90/1999, as amended) TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material Neoprene **Thickness (mm)** No data available **Breakthrough Time** No data available

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical prope	erties
Physical state	Solid
Specific Physical Form:	Paste
Appearance/Odor	Light cream colored paste with slight hydrocarbon odor
Odor threshold	No Data Available
рН	No Data Available
Boiling point/boiling range	198.9 ℃
Melting point	No Data Available
Flammability (solid, gas)	Flammable Solid: Category 1.
Explosive properties:	Not Classified
Oxidising properties:	Not Classified
Flash Point	65.6 °C
Autoignition temperature	No Data Available
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Relative Density	0.86 [<i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Evaporation rate	No Data Available
Vapor Density	No Data Available
Decomposition temperature	No Data Available
Viscosity	> 100 mPa-s
Density	0.86 g/cm3
Densky	
9.2. Other information	
EU Volatile Organic Compounds	No Data Available
Molecular weight	No Data Available
wolcoular weight	Νο Βαια Αναιιαθιε

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat Sparks and/or flames

10.5. Incompatible materials Strong oxidizing agents Strong acids

10.6. Hazardous decomposition products <u>Substance</u> None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphthol Spirits	Inhalation- Vapor		LC50 estimated to be 20 - 50 mg/l
Naphthol Spirits	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphthol Spirits	Ingestion	Rat	LD50 > 5,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 3,160 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	Dermal		LD50 estimated to be > 5,000 mg/kg
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	Ingestion	Rat	LD50 > 2,000 mg/kg
Siloxanes and Silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and Silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
CARNAUBA WAX	Dermal		LD50 estimated to be > 5,000 mg/kg
CARNAUBA WAX	Ingestion	Rat	LD50 > 8,800 mg/kg
PARAFFIN WAX	Dermal	Rat	LD50 > 5,000 mg/kg
PARAFFIN WAX	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Naphthol Spirits	Rabbit	Irritant
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
CARNAUBA WAX	Professio nal judgemen t	No significant irritation
PARAFFIN WAX	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Naphthol Spirits	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
CARNAUBA WAX	Professio	No significant irritation
	nal	
	judgemen	
	t	
PARAFFIN WAX	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Naphthol Spirits	Guinea	Not classified
	pig	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea	Not classified
	pig	
PARAFFIN WAX	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Naphthol Spirits	In vivo	Not mutagenic
Naphthol Spirits	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
PARAFFIN WAX	In Vitro	Not mutagenic

Carcinogenicity

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

Name	Route	Species	Value
Naphthol Spirits	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphthol Spirits	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
PARAFFIN WAX	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphthol Spirits	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphthol Spirits	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Naphthol Spirits	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Notavailable	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
Naphthol Spirits	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6	6 months
					mg/l	
Naphthol Spirits	Inhalation	kidney and/or	Not classified	Rat	LOAEL 1.9	13 weeks
		bladder			mg/l	
Naphthol Spirits	Inhalation	respiratory system	Not classified	Multiple	NOAEL 0.6	90 days

Naphthol Spirits	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	animal species Rat	mg/l NOAEL 5.6 mg/l	12 weeks
Naphthol Spirits	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
PARAFFIN WAX	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	90 days
PARAFFIN WAX	Ingestion	hematopoietic system liver immune system skin endocrine system bone, teeth, nails, and/or hair muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days

Aspiration Hazard

Name	Value
Naphthol Spirits	Aspiration hazard
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available

Naphthol	64742-48-9		Data not			
Spirits	01712 10 9		available or			
- I			insufficient for			
			classification			
HYDROTREA	64742-47-8	Water flea	Estimated	48 hours	Effect Level	1.4 mg/l
TED LIGHT					50%	
PETROLEUM						
DISTILLATES						
HYDROTREA	64742-47-8	Water flea	Estimated	21 days	No obs Effect	0.48 mg/l
TED LIGHT					Level	
PETROLEUM						
DISTILLATES						
HYDROTREA	64742-47-8	Rainbow Trout	Estimated	96 hours	Lethal Level	2 mg/l
TED LIGHT					50%	
PETROLEUM						
DISTILLATES HYDROTREA		Carry Alere	Estimated	72 hours	Effect	1 /1
TED LIGHT	04/42-4/-8	Green Algae	Estimated	72 nours	Concentration	1 mg/l
PETROLEUM					50%	
DISTILLATES					50%	
	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect	1 mg/l
TED LIGHT	04742-47-0	Oreen Algae	Lstimated	72 110013	Level	1 mg/1
PETROLEUM						
DISTILLATES						
FATTY	73138-45-1		Data not			
ACIDS,			available or			
MONTAN-			insufficient for			
WAX,			classification			
ETHYLENE						
ESTERS						
PARAFFIN	8002-74-2	Green algae	Experimental	96 hours	Effect	>1,000 mg/l
WAX					Concentration	
					50%	
PARAFFIN	8002-74-2	Water flea	Experimental	48 hours	Effect	>10,000 mg/l
WAX					Concentration	
	0002 74 2		Г (1	061	50%	. 1.000 /1
PARAFFIN	8002-74-2	Rainbow Trout	Experimental	96 hours	Lethal	>1,000 mg/l
WAX					Concentration 50%	
Siloxanes and	63148-62-9		Data not	+	5070	
Silicones, di-	03140-02-7		available or			
Me			insufficient for			
			classification			
CARNAUBA	8015-86-9		Data not	1		
WAX			available or			
			insufficient for			
			classification			

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
FATTY	73138-45-1	Data not	N/A	N/A	N/A	N/A

ACIDS, MONTAN- WAX, ETHYLENE ESTERS		available or insufficient for classification				
Naphthol Spirits	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREA TED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
PARAFFIN WAX	8002-74-2	Estimated Biodegradation	28 days	Biological Oxygen Demand	40 % weight	OECD 301F - Manometric Respiro
CARNAUBA WAX	8015-86-9	Modeled Biodegradation	28 days	Biological Oxygen Demand	82 % weight	OECD 301F - Manometric Respiro

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
HYDROTREA	64742-47-8	Data not	N/A	N/A	N/A	N/A
TED LIGHT		available or				
PETROLEUM		insufficient for				
DISTILLATES		classification				
FATTY	73138-45-1	Data not	N/A	N/A	N/A	N/A
ACIDS,		available or				
MONTAN-		insufficient for				
WAX,		classification				
ETHYLENE						
ESTERS						
Siloxanes and	63148-62-9	Data not	N/A	N/A	N/A	N/A
Silicones, di-		available or				
Me		insufficient for				
		classification				
Naphthol	64742-48-9	Data not	N/A	N/A	N/A	N/A
Spirits		available or				
		insufficient for				
		classification				

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

200113* Solvents

SECTION 14: Transportation information

IMDG: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; EMS: F-A, S-G. (ENG)

ADR: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; (E); F1.

IATA: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II. (ENG)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapor.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 02: CLP Ingredient table information was modified.

Section 03: Composition/ Information of ingredients table information was added.

Section 03: Composition/ Information of ingredients table information was deleted.

Section 08: Occupational exposure limit table information was modified.

Section 09: Property description for optional properties information was modified.

Section 09: Relative density information information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 14: Transportation classification information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use

(except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. Greece SDSs are available at GR_GCSL - Local Meguiar's Website