

Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 26-8072-6 **Version Number:** 1.05

Revision Date: 21/06/2017 **Supercedes Date:** 01/12/2016

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) and its modifications

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

D140, Wheel Brightener (26-86A): D14001, D14005, D14025, D14055

Product Identification Numbers

GC-8010-6286-7 KS-9990-0694-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive

1.3. Details of the supplier of the safety data sheet

ADDRESS: GR_GCSL - Local CUNO Address
Telephone: GR_GCSL - Local Meguiar's Telephone
E Mail: GR_GCSL - Local Meguiar's Email
Website: GR_GCSL - Local Meguiar's Website

1.4. Emergency telephone number

GR_GCSL - Local Meguiar's Emergency Telephone

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Substance or Mixture Corrosive to Metals, Category 1 - Met. Corr. 1; H290 Acute Toxicity, Category 4 - Acute Tox. 4; H302 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

Danger

Symbols:

GHS05 (Corrosion) | GHS07 (Exclamation mark) |

Pictograms





Ingredients:

Ingredient C.A.S. No. EC No. % by Wt

Ammonium Bifluoride 1341-49-7 215-676-4 5 - 10

HAZARD STATEMENTS:

H290 May be corrosive to metals. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P234 Keep only in original container.
P260E Do not breathe vapor or spray.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P310	Immediately call a POISON CENTER or doctor/physician.
Disposal:	
P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
4% of the mixture consists of comp	onents of unknown acute inhalation toxicity.
Notes on labelling: Updated per Regulation (EC) No. 6 Ingredients required per 648/2004 (abrightener.	48/2004 on detergents. not required on industrial label): <5%: Non-ionic surfactant. Contains: Perfume, optical

2.3. Other hazards

May cause chemical gastrointestinal burns. May cause chemical respiratory tract burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	EC No.	REACH	% by Wt	Classification
			Registration		
			No.		
Non-hazardous ingredients	7732-18-5	231-791-2		70 - 90	Substance not classified as
					hazardous
Ammonium Bifluoride	1341-49-7	215-676-4		5 - 10	**Acute Tox. 3**, H301;
					Skin Corr. 1B, H314
Na Xylene Sulfonate	1300-72-7	215-090-9		1 - 5	Substance not classified as
					hazardous
ETHOXYLATED C9-11 ALCOHOLS	68439-46-3			0.5 - 1.5	**Acute Tox. 4**, H302;
					Skin Irrit. 2, H315;
					Eye Dam. 1, H318
Ammonium Fluoride	12125-01-8	235-185-9		< 0.5	**Acute Tox. 3**, H331;
					Acute Tox. 3, H311;
					Acute Tox. 3, H301

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get immediate medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionHydrogen FluorideDuring CombustionIrritant Vapors or GasesDuring Combustion

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Absorb spillage to prevent material damage. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Collect the resulting residue containing solution. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents

(eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away from heat. Store in a corrosive resistant container with a resistant inner liner. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Applicable norms/standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimeButyl RubberNo data availableNo data available

Applicable norms/standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable norms/standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid

Appearance/Odor Water-thin purple liquid with sweet odor.

Odor threshold No Data Available

pH 4.5 - 5.5

Boiling point/boiling range 98.9 °C

Melting point Not Applicable

Flammability (solid, gas) Not Applicable

Explosive properties: Not Classified

Oxidising properties: Not Classified

Flash Point Flash point > 93 °C (200 °F) [Test Method: Closed Cup]

Autoignition temperatureNo Data AvailableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor PressureNo Data Available

Relative Density 1.04 - 1.07 [*Ref Std:* WATER=1]

Water solubility Complete

Solubility- non-water No Data Available

Partition coefficient: n-octanol/ waterNo Data AvailableEvaporation rateNo Data AvailableVapor DensityNo Data Available

Decomposition temperatureNo Data AvailableViscosityNo Data AvailableDensity1.04 g/cm3

9.2. Other information

Molecular weightNo Data AvailablePercent volatileNo Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids Strong bases Strong oxidizing agents

Reacts with metals/glass to form Hydrofluoric acid

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur. Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Corrosion: Signs/symptoms may include nasal discharge, severe nose and throat pain, chest tightness and pain, coughing up blood, wheezing, and breathlessness, possibly progressing to respiratory failure.

May cause additional health effects (see below).

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Prolonged or repeated exposure may cause target organ effects:

Hard Tissue Effects: Signs/symptoms may include color changes in the teeth and nails; changes in development of bone, teeth or nails; weakening of the bones; and/or hair loss.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-		No data available; calculated ATE5 - 12.5 mg/l
	Dust/Mist(4		

	hr)		
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
Ammonium Bifluoride	Inhalation-	Rat	LC50 0.74 mg/l
	Dust/Mist		
	(4 hours)		
Ammonium Bifluoride	Ingestion	Rat	LD50 60 mg/kg
Na Xylene Sulfonate	Dermal		LD50 estimated to be > 5,000 mg/kg
Na Xylene Sulfonate	Ingestion	Rat	LD50 > 5,000 mg/kg
ETHOXYLATED C9-11 ALCOHOLS	Dermal	Rabbit	LD50 > 2,000 mg/kg
ETHOXYLATED C9-11 ALCOHOLS	Ingestion	Rat	LD50 1,378 mg/kg
Ammonium Fluoride	Dermal		estimated to be 200 - 1,000 mg/kg
Ammonium Fluoride	Inhalation-		estimated to be 0.5 - 1 mg/l
	Dust/Mist		
Ammonium Fluoride	Ingestion		estimated to be 50 - 300 mg/kg

 \overline{ATE} = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ETHOXYLATED C9-11 ALCOHOLS	Rabbit	Irritant

Serious Eye Damage/Irritation

Serious 2, o 2 umage/1111uuron		
Name	Species	Value
ETHOXYLATED C9-11 ALCOHOLS	Professio	Corrosive
	nal	
	judgemen	
	t	

Skin Sensitization

Skin Schsitzation		
Name	Species	Value
ETHOXYLATED C9-11 ALCOHOLS	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

our management,		
Name	Route	Value
ETHOXYLATED C9-11 ALCOHOLS	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ETHOXYLATED C9-11 ALCOHOLS	Dermal	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
ETHOXYLATED C9-11 ALCOHOLS	Dermal	Not classified for development	Rat	NOAEL 250 mg/kg/day	2 generation
ETHOXYLATED C9-11 ALCOHOLS	Dermal	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

·· · · · · · · · · · · · · · · · · · ·		8 · · I · · · ·				
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
ETHOXYLATED C9-11	Inhalation	respiratory irritation	Some positive data exist, but the	Not	NOAEL Not	not available
ALCOHOLS			data are not sufficient for	available	available	
			classification			

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHOXYLATED C9-11 ALCOHOLS	Dermal	kidney and/or bladder hematopoietic system	Not classified	Rat	NOAEL 125 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Ammonium Bifluoride	1341-49-7		Data not available or insufficient for classification			
Ammonium Fluoride	12125-01-8		Data not available or insufficient for classification			
Ammonium Fluoride	12125-01-8	Fathead Minnow	Experimental	96 hours	Lethal Concentration 50%	364 mg/l
Ammonium Fluoride	12125-01-8	Grass Shrimp	Experimental	96 hours	Effect Concentration 50%	75 mg/l
Na Xylene Sulfonate	1300-72-7	Water flea	Experimental	48 hours	Effect Concentration 50%	>400 mg/l
Na Xylene Sulfonate	1300-72-7	Fathead Minnow	Experimental	96 hours	Lethal Concentration 50%	>400 mg/l
Na Xylene Sulfonate	1300-72-7	Green Algae	Experimental	96 hours	Effect Concentration 50%	230 mg/l
Na Xylene Sulfonate	1300-72-7	Green Algae	Experimental	96 hours	No obs Effect Conc	31 mg/l
ETHOXYLAT ED C9-11 ALCOHOLS	68439-46-3	Green algae	Experimental	72 hours	Effect Concentration 50%	45 mg/l
ETHOXYLAT ED C9-11 ALCOHOLS	68439-46-3	Fathead Minnow	Experimental	96 hours	Lethal Concentration 50%	8.5 mg/l
ETHOXYLAT ED C9-11 ALCOHOLS	68439-46-3	Water flea	Experimental	48 hours	Effect Concentration 50%	2.686 mg/l
ETHOXYLAT ED C9-11 ALCOHOLS	68439-46-3	Fathead Minnow	Experimental	30 days	No obs Effect Conc	0.73 mg/l
ETHOXYLAT ED C9-11 ALCOHOLS	68439-46-3	Green Algae	Experimental	72 hours	No obs Effect Conc	1.2 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Ammonium	1341-49-7	Data not	N/A	N/A	N/A	N/A
Bifluoride		available or				
		insufficient for				
		classification				
Na Xylene	1300-72-7	Experimental	28 days	Carbon dioxide	84 % weight	OECD 301B - Mod.
Sulfonate		Biodegradation		evolution		Sturm or CO2
ETHOXYLAT	68439-46-3	Experimental	28 days	Biological	88 % weight	OECD 301F -
ED C9-11		Biodegradation		Oxygen		Manometric Respiro
ALCOHOLS				Demand		_
Ammonium	12125-01-8	Data not	N/A	N/A	N/A	N/A
Fluoride		available or				
		insufficient for				
		classification				

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Ammonium	1341-49-7	Data not	N/A	N/A	N/A	N/A
Bifluoride		available or				
		insufficient for				
		classification				
Na Xylene	1300-72-7	Estimated	42 days	Bioaccumulatio	=<2.3	OECD 305E-Bioaccum
Sulfonate		BCF-Carp		n Factor		Fl-thru fis
ETHOXYLAT	68439-46-3	Estimated		Bioaccumulatio	33	Est: Bioconcentration
ED C9-11		Bioconcentrati		n Factor		factor
ALCOHOLS		on				
Ammonium	12125-01-8	Data not	N/A	N/A	N/A	N/A
Fluoride		available or				
		insufficient for				
		classification				

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available

The surfactant(s) contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Combustion products will include HF. Facility must be capable of handling halogenated materials.

Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

200129* Detergents containing dangerous substances

SECTION 14: Transportation information

ADR: UN2817; Ammonium Hydrogendifluoride, Solution; 8 (6.1); III; CT1.

IMDG: UN2817; Ammonium Hydrogendifluoride, Solution; 8 (6.1); III; EMS: FA, SB. (ENG)

IATA: UN2817; Ammonium Hydrogendifluoride, Solution; 8 (6.1); III. (ENG)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.

Revision information:

Section 02:	CLP	Ingredient	table inf	ormation	was modified.
Dection of		III SI COI CIIC	tuoic iiii	OIIII	" ab illouilleu.

- Section 03: Composition/Information of ingredients table information was added.
- Section 03: Composition/ Information of ingredients table information was deleted.
- Section 08: Appropriate Engineering controls information information was modified.
- Section 09: Flash point information information was modified.
- Section 09: Relative density information information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 13: Standard Phrase Category Waste GHS information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. Greece SDSs are available at GR_GCSL - Local Meguiar's Website