



Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	27-5146-9	Version Number:	1.03
Revision Date:	13/11/2017	Supersedes Date:	12/12/2016

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) and its modifications

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

G70, Gold Class Paste Car Wax (21-124A): G7014

Product Identification Numbers

14-1000-0911-8 14-1000-0912-6 14-1000-0913-4 14-1000-0915-9 HB-0041-3002-5
HB-0041-7033-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive

1.3. Details of the supplier of the safety data sheet

ADDRESS: GR_GCSL - Local CUNO Address
Telephone: GR_GCSL - Local Meguiar's Telephone
E Mail: GR_GCSL - Local Meguiar's Email
Website: GR_GCSL - Local Meguiar's Website

1.4. Emergency telephone number

GR_GCSL - Local Meguiar's Emergency Telephone

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

Danger

Symbols:

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	C.A.S. No.	EC No.	% by Wt
Naphthol Spirits	64742-48-9	265-150-3	30 - 60

HAZARD STATEMENTS:

H228	Flammable solid.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A Avoid breathing vapors.

Response:

P332 + P313 If skin irritation occurs: Get medical advice/attention.
P370 + P378G In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

13% of the mixture consists of components of unknown acute oral toxicity.

Contains 20% of components with unknown hazards to the aquatic environment.

Notes on labelling:

H304 is not required on the label due to the product's viscosity

Nota P applied to CASR 64742-48-9.

H228 assigned based on test data indicating that this product is a flammable solid.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	EC No.	REACH Registration No.	% by Wt	Classification
Naphthol Spirits	64742-48-9	265-150-3		30 - 60	**Asp. Tox. 1**, H304 - Nota P **Aquatic Chronic 2**, H411 **Skin Irrit. 2**, H315; **STOT SE 3**, H336
ORGANIC SALT (NJTSRN 04499600-6842)	Trade Secret			10 - 13	Substance with a Community level exposure limit in the workplace
Siloxanes and Silicones, di-Me	63148-62-9			7 - 13	Substance not classified as hazardous
Kaolin, calcined	92704-41-1	296-473-8		9 - 11	Substance not classified as hazardous
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	73138-45-1	277-291-8		1 - 10	Substance not classified as hazardous
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	265-149-8		3 - 7	**Asp. Tox. 1**, H304 **Aquatic Chronic 2**, H411 **Flam. Liq. 3**, H226; **Skin Irrit. 2**, H315; **STOT SE 3**, H336
MONTAN-WAX FATTY ACIDS	68476-03-9	270-664-6		1 - 5	Substance not classified as hazardous
GLYCEROL POLY(OXYETHYLENE, OXYPROPYLENE) ETHER	9082-00-2			1 - 2	Substance not classified as hazardous
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	68953-58-2	273-219-4		0 - 1	Substance not classified as hazardous
Anatase TiO2	1317-70-0	215-280-1		< 0.5	Substance with a Community level exposure limit in the workplace
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	232-455-8		0 - 0.5	**Asp. Tox. 1**, H304

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium oxide (TiO2)	1317-70-0	Greece OELs	TWA(Inhalable)(8 hours):10 mg/m3;TWA(respirable)(8 hours):5 mg/m3	
Naphthol Spirits	64742-48-9	Manufacturer determined	TWA:100 ppm	
Paraffin oil	8042-47-5	Greece OELs	TWA(as mist)(8 hours):5 mg/m3	

ORGANIC SALT (NJTSRN Trade Secret Greece OELs TWA(as AI)(8 hours):2 mg/m3
04499600-6842)
Greece OELs : Greece. OELs (Decree No. 90/1999, as amended)
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Neoprene	No data available	No data available

Applicable norms/standards

Use gloves tested to EN 374

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable norms/standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Solid
Specific Physical Form:	Paste
Appearance/Odor	Pleasant odor; Cream-colored paste
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Boiling point/boiling range	185 °C
Melting point	<i>Not Applicable</i>
Flammability (solid, gas)	Flammable Solid: Category 1.
Explosive properties:	Not Classified
Oxidising properties:	Not Classified
Flash Point	≥ 93.3 °C [<i>Test Method: Pensky-Martens Closed Cup</i>]
Autoignition temperature	<i>No Data Available</i>
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Relative Density	0.85 [<i>Ref Std: WATER=1</i>]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Evaporation rate	<i>No Data Available</i>

Vapor Density	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Density	0.85 g/cm ³

9.2. Other information

EU Volatile Organic Compounds	No Data Available
Molecular weight	No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

Strong acids
Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

G70, Gold Class Paste Car Wax (21-124A): G7014

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphthol Spirits	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Naphthol Spirits	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphthol Spirits	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and Silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	Dermal		LD50 estimated to be > 5,000 mg/kg
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	Ingestion	Rat	LD50 > 2,000 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 3,160 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
MONTAN-WAX FATTY ACIDS	Dermal		LD50 estimated to be > 5,000 mg/kg
MONTAN-WAX FATTY ACIDS	Ingestion	Rat	LD50 > 15,000 mg/kg
GLYCEROL POLY(OXYETHYLENE, OXYPROPYLENE) ETHER	Dermal	Rabbit	LD50 > 5,000 mg/kg
GLYCEROL POLY(OXYETHYLENE, OXYPROPYLENE) ETHER	Ingestion	Rat	LD50 > 10,000 mg/kg
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	Dermal		LD50 estimated to be > 5,000 mg/kg
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 12.6 mg/l
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	Ingestion	Rat	LD50 > 5,000 mg/kg
WHITE MINERAL OIL (PETROLEUM)	Dermal	Rabbit	LD50 > 2,000 mg/kg
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
Anatase TiO2	Dermal	Rabbit	LD50 > 10,000 mg/kg
Anatase TiO2	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Anatase TiO2	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Naphthol Spirits	Rabbit	Irritant
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	Rat	No significant irritation
WHITE MINERAL OIL (PETROLEUM)	Rabbit	No significant irritation
Anatase TiO2	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Naphthol Spirits	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation

G70, Gold Class Paste Car Wax (21-124A): G7014

HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	Rabbit	No significant irritation
WHITE MINERAL OIL (PETROLEUM)	Rabbit	Mild irritant
Anatase TiO ₂	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Naphthol Spirits	Guinea pig	Not classified
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea pig	Not classified
WHITE MINERAL OIL (PETROLEUM)	Guinea pig	Not classified
Anatase TiO ₂	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Naphthol Spirits	In vivo	Not mutagenic
Naphthol Spirits	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
WHITE MINERAL OIL (PETROLEUM)	In Vitro	Not mutagenic
Anatase TiO ₂	In Vitro	Not mutagenic
Anatase TiO ₂	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Naphthol Spirits	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphthol Spirits	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
WHITE MINERAL OIL (PETROLEUM)	Dermal	Mouse	Not carcinogenic
WHITE MINERAL OIL (PETROLEUM)	Inhalation	Multiple animal species	Not carcinogenic
Anatase TiO ₂	Ingestion	Multiple animal species	Not carcinogenic
Anatase TiO ₂	Inhalation	Rat	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
WHITE MINERAL OIL (PETROLEUM)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphthol Spirits	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphthol Spirits	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Naphthol Spirits	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Naphthol Spirits	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Naphthol Spirits	Inhalation	respiratory system	Not classified	Multiple	NOAEL 0.6	90 days

G70, Gold Class Paste Car Wax (21-124A): G7014

				animal species	mg/l	
Naphthol Spirits	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Naphthol Spirits	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
WHITE MINERAL OIL (PETROLEUM)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
WHITE MINERAL OIL (PETROLEUM)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Anatase TiO2	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Anatase TiO2	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Naphthol Spirits	Aspiration hazard
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
WHITE MINERAL OIL (PETROLEUM)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Naphthol Spirits	64742-48-9	Green Algae	Estimated	72 hours	Effect Level 50%	3.1 mg/l
Naphthol Spirits	64742-48-9	Water flea	Estimated	48 hours	Effect Level 50%	4.5 mg/l

G70, Gold Class Paste Car Wax (21-124A): G7014

Naphthol Spirits	64742-48-9	Fathead Minnow	Estimated	96 hours	Lethal Level 50%	8.2 mg/l
Naphthol Spirits	64742-48-9	Water flea	Estimated	21 days	No obs Effect Level	2.6 mg/l
Naphthol Spirits	64742-48-9	Green Algae	Estimated	72 hours	No obs Effect Level	0.5 mg/l
ORGANIC SALT (NJTSRN 04499600-6842)	Trade Secret		Data not available or insufficient for classification			
Siloxanes and Silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
Kaolin, calcined	92704-41-1	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
Kaolin, calcined	92704-41-1	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	No obs Effect Conc	>100 mg/l
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	73138-45-1		Data not available or insufficient for classification			
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Rainbow Trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green Algae	Estimated	72 hours	Effect Concentration 50%	1 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
MONTAN-WAX FATTY ACIDS	68476-03-9	Zebra Fish	Experimental	96 hours	Lethal Concentration 50%	>500 mg/l
GLYCEROL POLY(OXYETHYLENE, OXYPROPYLENE) ETHER	9082-00-2	Inland Silverside	Estimated	96 hours	Lethal Concentration 50%	650 mg/l
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	68953-58-2	Zebra Fish	Estimated	96 hours	Lethal Concentration 50%	>100 mg/l
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	68953-58-2	Water flea	Estimated	48 hours	Effect Concentration 50%	>100 mg/l
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH	68953-58-2	Green algae	Estimated	72 hours	Effect Concentration 50%	>100 mg/l

G70, Gold Class Paste Car Wax (21-124A): G7014

BENTONITE						
Anatase TiO2	1317-70-0		Data not available or insufficient for classification			
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Naphthol Spirits	64742-48-9	Estimated Biodegradation	28 days	Biological Oxygen Demand	10 % BOD/ThBOD	OECD 301D - Closed Bottle Test
ORGANIC SALT (NJTSRN 04499600-6842)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	73138-45-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
MONTAN-WAX FATTY ACIDS	68476-03-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
GLYCEROL POLY(OXYETHYLENE, OXYPROPYLENE) ETHER	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	68953-58-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Anatase TiO2	1317-70-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 % weight	OECD 301B - Mod. Sturm or CO2

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Naphthol Spirits	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ORGANIC SALT (NJTSRN 04499600-6842)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
FATTY ACIDS, MONTAN-WAX, ETHYLENE ESTERS	73138-45-1	Estimated Bioconcentration		Bioaccumulation Factor	20.5	Other methods
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
MONTAN-WAX FATTY ACIDS	68476-03-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
GLYCEROL POLY(OXYETHYLENE, OXYPROPYLENE) ETHER	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	68953-58-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Anatase TiO2	1317-70-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
WHITE MINERAL OIL (PETROLEUM)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

G70, Gold Class Paste Car Wax (21-124A): G7014

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

200113* Solvents

SECTION 14: Transportation information

IMDG: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; EMS: FA, SG (ENG)

ADR: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; (E); F1

IATA: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II. (ENG)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient
Anatase TiO₂

C.A.S. No.
1317-70-0

Classification
Grp. 2B: Possible human
carc.

Regulation
International Agency
for Research on Cancer

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

H226	Flammable liquid and vapor.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Section 01: Product identification numbers information was added.
Section 02: CLP Ingredient table information was modified.
Section 02: Label Elements: CLP Classification information was modified.
Section 02: Label Elements: CLP Environmental Hazard Statements information was added.
Section 02: Label Elements: CLP Percent Unknown information was modified.
Section 02: Label Elements: Graphic information was modified.
Section 03: Composition/ Information of ingredients table information was added.
Section 03: Composition/ Information of ingredients table information was deleted.
Section 06: Accidental release clean-up information information was modified.
Section 07: Precautions safe handling information information was modified.
Section 08: Occupational exposure limit table information was modified.
Section 09: Flash point information information was modified.
Section 09: Property description for optional properties information was modified.
Section 09: Relative density information information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 14: Transportation classification information was modified.
Section 15: Carcinogenicity information information was added.
Section 16: Two-column table displaying the unique list of H Codes and statements (std phrses) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. Greece SDSs are available at [GR_GCSL](#) - Local Meguiar's Website