



Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	33-5752-2	Version Number:	1.00
Revision Date:	19/07/2017	Supersedes Date:	Initial Issue

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) and its modifications

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

G85, Glass Treatment (22-131C): G8508

Product Identification Numbers

14-1000-9188-4 14-1001-0139-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive

1.3. Details of the supplier of the safety data sheet

ADDRESS: GR_GCSL - Local CUNO Address
Telephone: GR_GCSL - Local Meguiar's Telephone
E Mail: GR_GCSL - Local Meguiar's Email
Website: GR_GCSL - Local Meguiar's Website

1.4. Emergency telephone number

GR_GCSL - Local Meguiar's Emergency Telephone

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Aspiration Hazard, Category 1 - Asp. Tox. 1; H304
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

Danger

Symbols:

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	C.A.S. No.	EC No.	% by Wt
Isopropyl Alcohol	67-63-0	200-661-7	40 - 70
Petroleum Distillates	64742-47-8	265-149-8	10 - 30

HAZARD STATEMENTS:

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102	Keep out of reach of children.
------	--------------------------------

Prevention:

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION**Supplemental Hazard Statements:**

EUH066 Repeated exposure may cause skin dryness or cracking.

1% of the mixture consists of components of unknown acute oral toxicity.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	EC No.	REACH Registration No.	% by Wt	Classification
Isopropyl Alcohol	67-63-0	200-661-7		40 - 70	**Flam. Liq. 2**, H225; **Eye Irrit. 2**, H319; **STOT SE 3**, H336
Petroleum Distillates	64742-47-8	265-149-8		10 - 30	**Asp. Tox. 1**, H304 **Aquatic Chronic 2**, H411 **Flam. Liq. 3**, H226; **STOT SE 3**, H336; **EUH066**, EUH066
Poly(Dimethylsiloxane)	63148-62-9			5 - 15	Substance not classified as hazardous
1-Propoxy-2-Propanol	1569-01-3	216-372-4		7 - 13	**Flam. Liq. 3**, H226; **Eye Irrit. 2**, H319; **STOT SE 3**, H336; **EUH066**, EUH066
Sulfuric Acid	7664-93-9	231-639-5		0.5 - 1.5	**Skin Corr. 1A**, H314 - Nota B

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes
Formaldehyde
Carbon monoxide
Carbon dioxide
Oxides of Sulfur

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the

container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Isopropyl Alcohol	67-63-0	Greece OELs	TWA(8 hours):980 mg/m3(400 ppm);STEL(15 minutes):1225 mg/m3(500 ppm)	
Sulfuric Acid	7664-93-9	Greece OELs	TWA(mist, thoracic fraction)(8 hours):0.05 mg/m3	

Greece OELs : Greece. OELs (Decree No. 90/1999, as amended)

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Applicable norms/standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Neoprene	No data available	No data available
Nitrile Rubber	No data available	No data available

Applicable norms/standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable norms/standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance/Odor	translucent liquid with characteristic chemical odor
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Boiling point/boiling range	80 - 90 °C
Melting point	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Explosive properties:	Not Classified
Oxidising properties:	Not Classified
Flash Point	12.8 °C [<i>Test Method</i> :Closed Cup]
Autoignition temperature	<i>No Data Available</i>
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Relative Density	0.82 [<i>Ref Std</i> :WATER=1]
Water solubility	<i>No Data Available</i>
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Evaporation rate	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	10 mPa-s
Density	0.82 g/ml

9.2. Other information

EU Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	87.4 % weight [<i>Test Method</i> :Estimated]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

Strong acids

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapor (4	Rat	LC50 72.6 mg/l

G85, Glass Treatment (22-131C): G8508

	hours)		
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
1-Propoxy-2-Propanol	Dermal	Rabbit	LD50 2,805 mg/kg
1-Propoxy-2-Propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 11.8 mg/l
1-Propoxy-2-Propanol	Ingestion	Rat	LD50 2,500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isopropyl Alcohol	Multiple animal species	No significant irritation
Petroleum Distillates	Rabbit	Mild irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
1-Propoxy-2-Propanol	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Isopropyl Alcohol	Rabbit	Severe irritant
Petroleum Distillates	Rabbit	Mild irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
1-Propoxy-2-Propanol	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
Isopropyl Alcohol	Guinea pig	Not classified
Petroleum Distillates	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic

G85, Glass Treatment (22-131C): G8508

Petroleum Distillates	In Vitro	Not mutagenic
1-Propoxy-2-Propanol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
1-Propoxy-2-Propanol	Inhalation	Not classified for development	Rat	NOAEL 3.6 mg/l	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
1-Propoxy-2-Propanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	LOAEL 10.8 mg/l	6 hours
1-Propoxy-2-Propanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1-Propoxy-2-Propanol	Ingestion	central nervous	May cause drowsiness or	Rat	LOAEL	not applicable

G85, Glass Treatment (22-131C): G8508

		system depression	dizziness		1,770 mg/kg	
--	--	-------------------	-----------	--	-------------	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
1-Propoxy-2-Propanol	Inhalation	liver kidney and/or bladder	Not classified	Rat	NOAEL 9.5 mg/l	11 days

Aspiration Hazard

Name	Value
Petroleum Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Isopropyl Alcohol	67-63-0	Ricefish	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Isopropyl Alcohol	67-63-0	Green Algae	Experimental	72 hours	Effect Concentration 50%	>1,000 mg/l

G85, Glass Treatment (22-131C): G8508

Isopropyl Alcohol	67-63-0	Crustacea	Experimental	24 hours	Effect Concentration 50%	>10,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	48 hours	Effect Concentration 50%	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	21 days	No obs Effect Conc	>=100 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	No obs Effect Conc	1,000 mg/l
Petroleum Distillates	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Petroleum Distillates	64742-47-8	Rainbow Trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Petroleum Distillates	64742-47-8	Green Algae	Estimated	72 hours	Effect Concentration 50%	1 mg/l
Petroleum Distillates	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Petroleum Distillates	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Poly(Dimethylsiloxane)	63148-62-9		Data not available or insufficient for classification			
1-Propoxy-2-Propanol	1569-01-3	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
1-Propoxy-2-Propanol	1569-01-3	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
1-Propoxy-2-Propanol	1569-01-3	Green Algae	Experimental	96 hours	Effect Concentration 50%	1,466 mg/l
Sulfuric Acid	7664-93-9	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
Sulfuric Acid	7664-93-9	Green algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
Sulfuric Acid	7664-93-9	Green algae	Experimental	72 hours	No obs Effect Conc	100 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Biodegradation	14 days	Biological Oxygen Demand	86 % weight	OECD 301C - MITI (I)
Petroleum Distillates	64742-47-8	Data not available or	N/A	N/A	N/A	N/A

G85, Glass Treatment (22-131C): G8508

		insufficient for classification				
Poly(Dimethylsiloxane)	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1-Propoxy-2-Propanol	1569-01-3	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	91.5 % weight	OECD 301A - DOC Die Away Test
Sulfuric Acid	7664-93-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	0.05	Other methods
Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly(Dimethylsiloxane)	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1-Propoxy-2-Propanol	1569-01-3	Estimated Bioconcentration		Bioaccumulation Factor	3	Est: Bioconcentration factor
Sulfuric Acid	7664-93-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

080111* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. Greece SDSs are available at [GR_GCSL](#) - Local Meguiar's Website