



## Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	28-4940-4	<b>Version Number:</b>	2.01
<b>Revision Date:</b>	12/07/2017	<b>Supersedes Date:</b>	24/11/2016

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) and its modifications

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

M16, Mirror Glaze Professional Paste Wax (27-03A): M1611

#### Product Identification Numbers

14-1000-1185-8

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive

#### 1.3. Details of the supplier of the safety data sheet

**ADDRESS:** GR\_GCSL - Local CUNO Address  
**Telephone:** GR\_GCSL - Local Meguiar's Telephone  
**E Mail:** GR\_GCSL - Local Meguiar's Email  
**Website:** GR\_GCSL - Local Meguiar's Website

#### 1.4. Emergency telephone number

GR\_GCSL - Local Meguiar's Emergency Telephone

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

#### CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

Danger

#### Symbols:

GHS02 (Flame) | GHS07 (Exclamation mark) |

#### Pictograms



#### Ingredients:

Ingredient	C.A.S. No.	EC No.	% by Wt
Naphthol Spirits	64742-48-9	265-150-3	30 - 60
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	265-114-7	10 - 30

#### HAZARD STATEMENTS:

H228	Flammable solid.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

#### PRECAUTIONARY STATEMENTS

##### General:

P102	Keep out of reach of children.
------	--------------------------------

##### Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A	Avoid breathing vapors.

##### Response:

<b>M16, Mirror Glaze Professional Paste Wax (27-03A): M1611</b>
---

P332 + P313  
P370 + P378G

If skin irritation occurs: Get medical advice/attention.  
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Disposal:**

P501                      Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Contains 87% of components with unknown hazards to the aquatic environment.

**Notes on labelling:**

H304 is not required on the label due to the product's viscosity  
Nota P applied for CASRN 64742-48-9.

**2.3. Other hazards**

None known

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	EC No.	REACH Registration No.	% by Wt	Classification
Naphthol Spirits	64742-48-9	265-150-3		30 - 60	**Asp. Tox. 1**, H304 - Nota P **Aquatic Chronic 2**, H411 **Skin Irrit. 2**, H315; **STOT SE 3**, H336
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	265-114-7		10 - 30	Nota N **Asp. Tox. 1**, H304; **STOT SE 3**, H336; **EUH066**, EUH066
OXIDIZED POLYETHYLENE	68441-17-8			5 - 10	Substance not classified as hazardous
Fatty acids, montan-wax, ethylene esters	73138-45-1	277-291-8		5 - 10	Substance not classified as hazardous
Siloxanes and Silicones, di-Me	63148-62-9			5 - 10	Substance not classified as hazardous
CARNAUBA WAX	8015-86-9	232-399-4		5 - 10	Substance not classified as hazardous

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish. Water spray or fog may be used. Do not use straight streams.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Formaldehyde  
Carbon monoxide  
Carbon dioxide  
Irritant Vapors or Gases

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.3. Advice for fire-fighters**

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

**6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Naphthol Spirits	64742-48-9	Manufacturer determined	TWA:100 ppm	

Greece OELs : Greece. OELs (Decree No. 90/1999, as amended)

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

<b>Material</b>	<b>Thickness (mm)</b>	<b>Breakthrough Time</b>
Neoprene	No data available	No data available

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Appearance/Odor	Blue; hydrocarbon odor
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Boiling point/boiling range	171.1 °C
Melting point	<i>Not Applicable</i>
Flammability (solid, gas)	Flammable Solid: Category 1.
Explosive properties:	Not Classified
Oxidising properties:	Not Classified
Flash Point	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Relative Density	0.86 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Evaporation rate	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	$\geq 100$ mPa-s
Density	0.86 g/cm <sup>3</sup>

### 9.2. Other information

EU Volatile Organic Compounds	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.



#### 10.4. Conditions to avoid

Heat  
Sparks and/or flames

#### 10.5. Incompatible materials

Strong acids  
Strong bases  
Strong oxidizing agents

#### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 11.1. Information on Toxicological effects

##### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

##### Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

##### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

##### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphthol Spirits	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Naphthol Spirits	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphthol Spirits	Ingestion	Rat	LD50 > 5,000 mg/kg
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Dermal	Rabbit	LD50 > 2,000 mg/kg
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and Silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
CARNAUBA WAX	Dermal		LD50 estimated to be > 5,000 mg/kg
Fatty acids, montan-wax, ethylene esters	Dermal		LD50 estimated to be > 5,000 mg/kg
CARNAUBA WAX	Ingestion	Rat	LD50 > 8,800 mg/kg
Fatty acids, montan-wax, ethylene esters	Ingestion	Rat	LD50 > 2,000 mg/kg
OXIDIZED POLYETHYLENE	Ingestion	Rat	LD50 > 2,500 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Naphthol Spirits	Rabbit	Irritant
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Professio	Mild irritant

**M16, Mirror Glaze Professional Paste Wax (27-03A): M1611**

	nal judgemen t	
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
CARNAUBA WAX	Professio nal judgemen t	No significant irritation
OXIDIZED POLYETHYLENE	Professio nal judgemen t	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Naphthol Spirits	Rabbit	No significant irritation
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Professio nal judgemen t	Mild irritant
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
CARNAUBA WAX	Professio nal judgemen t	No significant irritation
OXIDIZED POLYETHYLENE	Professio nal judgemen t	No significant irritation

**Skin Sensitization**

Name	Species	Value
Naphthol Spirits	Guinea pig	Not classified
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Naphthol Spirits	In vivo	Not mutagenic
Naphthol Spirits	In Vitro	Some positive data exist, but the data are not sufficient for classification
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	In Vitro	Not mutagenic

**M16, Mirror Glaze Professional Paste Wax (27-03A): M1611****Carcinogenicity**

Name	Route	Species	Value
Naphthol Spirits	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphthol Spirits	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphthol Spirits	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphthol Spirits	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Naphthol Spirits	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Naphthol Spirits	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months

**M16, Mirror Glaze Professional Paste Wax (27-03A): M1611**

Naphthol Spirits	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Naphthol Spirits	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphthol Spirits	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Naphthol Spirits	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days

**Aspiration Hazard**

Name	Value
Naphthol Spirits	Aspiration hazard
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Fatty acids, montan-wax, ethylene esters	73138-45-1		Data not available or insufficient for classification			
Siloxanes and Silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
OXIDIZED POLYETHYL	68441-17-8		Data not available or			

**M16, Mirror Glaze Professional Paste Wax (27-03A): M1611**

ENE			insufficient for classification			
CARNAUBA WAX	8015-86-9		Data not available or insufficient for classification			
Naphthol Spirits	64742-48-9		Data not available or insufficient for classification			
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9		Data not available or insufficient for classification			
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9		Insufficient to classify			

**12.2. Persistence and degradability**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
OXIDIZED POLYETHYLENE	68441-17-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphthol Spirits	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
CARNAUBA WAX	8015-86-9	Modeled Biodegradation	28 days	Biological Oxygen Demand	82 % weight	OECD 301F - Manometric Respiro
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, montan-wax, ethylene esters	73138-45-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
CARNAUBA WAX	8015-86-9	Estimated Biodegradation	28 days	Carbon dioxide evolution	96 % weight	OECD 301B - Mod. Sturm or CO2

### 12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Naphthol Spirits	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
OXIDIZED POLYETHYLENE	68441-17-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
CARNAUBA WAX	8015-86-9	Modeled Bioaccumulation		Log of Octanol/H <sub>2</sub> O part. coeff	23.45	Other methods
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, montan-wax, ethylene esters	73138-45-1	Estimated Bioconcentration		Bioaccumulation Factor	20.5	Other methods
CARNAUBA WAX	8015-86-9	Estimated Bioconcentration		Bioaccumulation Factor	7.4	Est: Bioconcentration factor

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

### 12.6. Other adverse effects

No information available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective

**M16, Mirror Glaze Professional Paste Wax (27-03A): M1611**

regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

**EU waste code (product as sold)**

080111*	Waste paint and varnish containing organic solvents or other dangerous substances
200113*	Solvents

**SECTION 14: Transportation information**

IATA: UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S. (PETROLEUM DISTILLATE), 4.1, II.

ADR: UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S. (PETROLEUM DISTILLATE), 4.1, II, F1

IMDG: UN1325, FLAMMABLE SOLID, ORGANIC, N.O.S. (PETROLEUM DISTILLATE), 4.1, II, EmS: F-A S-G.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

**15.2. Chemical Safety Assessment**

Not applicable

**SECTION 16: Other information****List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.



**Revision information:**

Section 02: CLP Ingredient table information was modified.

Section 03: Composition/ Information of ingredients table information was added.

Section 03: Composition/ Information of ingredients table information was deleted.

Section 09: Flash point information information was added.

Section 09: Property description for optional properties information was modified.

Section 09: Relative density information information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 16: Two-column table displaying the unique list of H Codes and statements (std phrses) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**Meguiar's, Inc. Greece SDSs are available at [GR\\_GCSL](#) - Local Meguiar's Website**